



Zhitao Group
ZHITAO GROUP

Industrial Power Supplies

Product Specifications


ZTG-4000

- Product Category: 4000W Single Output Switching Power Supply
- Version No.: ZTAO3.0
- Release date: 1st May 2025

product overview

ZTG-4000-XX series products is a 4000W chassis type industrial power supply, the output voltage includes 12V/24V/36V/48V/72V/110V/220V, etc., can be adapted to different load application requirements to meet the needs of most industrial applications, built-in multi-functional such as output voltage, output current, remote on/off control, 485 communication control auxiliary power supply and other functions to provide a variety of design flexibility, fan cooling, as well as a full range of protections, to ensure that this series of products of reliability and stability.

Model Encoding



product characteristics

- AC input range 180~264VAC
- Type of protection: short circuit/overload/over temperature
- remote on/off control
- fan cooling
- Power on LED indicator
- 100% full load burn-in test
- 3-year warranty



RoHS



areas of application

Industrial control, mechanical and electrical, electronic instruments, industrial automation, electronic equipment, UV curing equipment, semiconductor equipment, etc. (except information technology equipment)

01-01






Zhitao Power Supply - is not just a full power supply

400-888-6287

electrical specifications

Model		ZTG-4000-12	ZTG-4000-24	ZTG-4000-36	ZTG-4000-48	ZTG-4000-72	ZTG-4000-110	ZTG-4000-220
Output	DC output voltage	12V	24V	36V	48V	72V	110V	220V
	Rated current	290A	166.7A	111A	83.3A	55.6A	36.4A	18.2A
	Current range	0~290A	0~166.7A	0~111A	0~83.3A	0~55.6A	0~36.4A	0~18.2A
	Rated power	3480W	4000.8W	3996W	3998.4W	4003.2W	4004W	4004W
	Ripple & Noise (Max)	250mVp-p	270mVp-p	300mVp-p	400mVp-p	500mVp-p	850mVp-p	1000mVp-p
	Output Voltage Adjustment	0~13.2V	0~26.4V	0~39.6V	0~52.8V	0~79.2V	0~121V	0~242V
	voltage accuracy	±1%	±1%	±1%	±1%	±1%	±1%	±1%
	Linear adjustment rate	±1%	±1%	±1%	±1%	±1%	±1%	±1%
	Load Adjustment Ratio	±1%	±1%	±1%	±1%	±1%	±1%	±1%
	start-up & rise time	1500ms,100ms/230VAC (at full load)						
Input	Input Voltage	180~264VAC 245~370VDC						
	Input frequency	45~65HZ						
	Efficiency	83%	86%	87%	89%	90%	90%	91%
	Input current	44A/230VAC						
	Leakage current	< 3.0mA/240VAC						
Protection	short-circuit protected	Protection mode: constant current limitation, restart recovery after removal of abnormal conditions						
	Over temperature	Turn off the output voltage, and recover automatically when the temperature drops or restart to recover						
Function	constant current optimum range	6~12V	12~24V	18~36V	24~48V	36~72V	55~110V	110~220V
	External potentiometer	External potentiometer control (voltage, current)						
	analogue signal control	0~5V/0~10V,0~5A/0~10A control(voltage,current)						
	Auxiliary power supply	12V 0.5A						
	Remote on/off control	Default power on, high level power off (3~12V)						
	Fan On/Off Control (Typ.)	The fan's spinning straight up						
Environment	Operating temperature	-20°C ~+60°C						
	Operating humidity	20~90%RH No condensation						
	Storage temperature/humidity	-40~+80°C 10~95%RH, no condensation						
Security	Vibration-resistant	10~500HZ, 5G 10 min/cycle, X, Y, Z 60 min each						
	pressure resistance	Input to Output :1.5KVAC; Input to Ground :1.5KVAC; Output to Ground :500VAC						
	Insulation impedance	Input to Output, Input to Ground, Output to Ground :100 Ohms/500VDC/25°C /70%RH						
Others	Product dimensions	300*200*70mm (L*W*H)						
	Packaging	4.1kg/pcs						
Remarks		1. All parameters are measured at 230VAC input, rated load and 25°C when not otherwise specified. 2. Ripple and noise voltages were measured on a 20MHz bandwidth oscilloscope with 0.1μ and 47μ capacitors at the end of a 12-inch twisted pair cable, measured at 20MHz bandwidth. 3. Accuracy: Includes setting error, linear adjustment ratio and load adjustment ratio. 4. Linear Adjustment Ratio Measurement Method: Test from low voltage to high voltage at rated load 5. Load Adjustment Ratio Measurement Method: From 0% to 100% of rated load 6. Start-up time is measured at cold start, fast and frequent switching on and off may increase the start-up time. 7. When operating at altitudes higher than 2000 metres (6500ft): the operating environment needs to be reduced by 5°C / 1000 metres						

Outline and Mounting Dimensions (mm)



Pinout	Function	
L	AC LINE	Screw:M4*11 Torque:22Kgf.cn(2.2N.m)
N	AC NETURAL	
⊕	EARTH	
-Vo	DC output -	Screw:M6*14 Torque:30Kgf.cn(3.0N.m)
-Vo	DC output -	
+Vo	DC output +	
+Vo	DC output +	

8-M4 Customer system

mounting holes

mounting screws: M4

Installation torque: 8Kgf.cn

(0.8N.m) screws into the housing


is not more than 3mm

Remarks:


Unit: mm [inch]; unlabelled tolerances are ± 0.5 [± 0.020].

Characteristic Curve

Input Voltage VS Output Load



Ambient Temperature VS Output Load



Remarks:

- 1.If you need to know more detailed test data, please contact our technical support to get the application notes of the corresponding products.
- 2.This product is suitable for use in a natural air convection environment, if used in a closed environment, please contact our technical support staff.